DURATECH® nodel 9564

[horizontal grinder]



DURATECH....Clearing the way for a better tomorrow.

The Model 9564 Horizontal Grinder is the newest member to the DuraTech Line up of industrial grinders. It comes with the CAT C27 Tier II Diesel engine that puts out 1050 HP (782.9 kw)

The HPTO wet clutch transfers power to the 64 inch wide 12,100 lb(5488.5 kg) hammermill. The hammermill is fed by a self governing floor apron and feed roller through a 60"(152.4cm) wide x 40" (101.6cm) high feed opening. The high capacity 315 cu. Ft. (11.66 cu. yd.) (8.91cu.m.) hopper will handle the largest trees and stumps.

Features Include:

- Caterpillar C27 1050 HP (782.9 kw) Tier II diesel engine.
- PT-Tech HPTO 15 microprocessor controlled wet clutch.
- Enclosed engine compartment with convenient access doors
- Self cleaning air intake system
- 30 ft. x 48 in. wide oscillating stacking conveyor.
- 10 groove belt drive connects the wet clutch to the hammermill.
- 12,100 pound (5488.47kg) 64 in. wide hammermill
- 24 hammers with a tip swing of 51 in.(129.54cm)
- 60 in.(152.4cm) wide x 40 in. high(101.6cm) feed opening.
- Self governing floor apron and feed roller (42 in.(106.68cm) diameter).
- Large 315 cu. Ft. (11.66Cu. YD.)(8.91Cu M) hopper; 61.5 in. (156.2cm) wide x 248 in. (629.9cm) long.
- Four Hydraulic stabilizer legs
- 91,500 pounds (41,503.7kg) of well engineered construction.

WWW. DURATECHINDUSTRIES.net [horizontal grinder]



Self Cleaning Air İntake System



Self Governing Apron and Feed Roller Feed Large Hammermill



Oscillating Stacking Conveyor Pivots 40 Degrees




10 Groove Belt Drive System



12,100 lb. (5,488.47kg) Hammermill



 \overline{HPTO} Wet Clutch





ECIFICATIONS

model 9564 [horizontal grinder]

Machine Dimensions

Tranport Length 53' (16.15m) Tranport Width 11' 10" (3.61m) Tranport Height 13' 5" (4.09m)

Axle/ Suspension

Spacing 57-1/2" (146.05cm/1.46m) 5th Wheel Weight 33,750lbs (15,308.74kg) Total Axle Weight 57,750lbs (26,195kg) 91,500lbs (41,503.7kg) Total Machine Weight

Drive System

Caterpillar C27 Tier II 1050HP (782.9kw) Diesel Engine Engine Clutch HPTO 15 TD Wet Clutch 380 Gallons / 1440 Litres Fuel Tank Fuel Consumption 45.7 gal./hr (179.8 L/hr) Hydraulic Tank 145 Gallons (548.9L) Rotor Drive 10 Groove 8V

Feed System

Hopper Capacity Hopper Width 315 Cubic Feet / 11.66 Yards (8.91cu.m.) 61-1/2" (156.2cm)Bottom / 74'

(187.7cm)Top

Hopper Length 248" (629.9cm)Door Up / 300"(762.0cm)Door Down

Hopper Depth 35" (88.9cm)

Feed Opening 61-1/2" x 40" (106.6cm x156.2cm)

Feed Height 96" (234.8cm)

Governing System Electric (PLC)

Programable Logic Controller Hydraulic Drives Two Load Sensing Pumps

Hammermill

Rotor Shaft Size 5-7/16" (13.81cm) Rotor Width 64" (162.6cm) 1125 RPM Rotor Speed Tip Swing Diameter 50-3/4" (126.9cm)

Number of Tips Cylinder Mid Plates 1-1/2" (3.81cm) Thick x

39" (99.06cm) Diameter Cylinder End Plates 1-1/2" (3.81cm)Thick x 40"(101.6cm) Diameter T-1 Material

12,100lbs (5488.47kg) Weight Hammer Rod Size 3-1/4" (8.26cmn)

Feed Roll

Rotor Diameter

Dual Orbit Motor/Double Reduction Gearboxes Drive

Screens

4340 Square Inches (11023.6 sq. cm) 1" (2.54cm) Screen Area Thickness

Hole Sizes Available in a variety of sizes **Belly Conveyor**

28-1/2' (8.69m) Length Width 54" (137.2cm)

Stacking Conveyor

366" / 30-1/2' (929.6cm/9.3m) Length

48" (121.9cm) 40° Side to Side Oscillation

22' (6.71m) @ 30 Degree Incline Stacking Height

Options

Air Compressor Magnetic Roller Multi-Function Remote Control Available

The PLC (Programable Logic Controller) regulates feed rate based on rotor speed.

Feed rate is proportional to rotor speed. Maximum feed rate is adjustable."Hammermill weight consists of shaft, hammer rods, bits, hardware and tool holders."

Illustrations, specifications, and descriptions contained herein were accurate at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories and may not include all standard equipment.



....Clearing the way for a better tomorrow.

3780 Hwy 281 SE, Jamestown, ND 58401 Phone: 1-800-243-4601 duratechindustries.net

